




LIXIO® MCROTERRAZZO





WHATIS LIXIO®

- ✓ LIXIO® is a polymer modified cement based microterrazzo. Using LIXIO® it is possible to create high-end polished surfaces.
- ✓ High quality Italian marble aggregates are used tooffer a prestigious and modern floor.
- ✓With only 4-7 mm thickness it is possible to create a highly abrasion-resistant surface, ideal for commercial and residential areas such as shops, restaurants, hotels, museum and private villas.







TEST RESULT

TEST		NORMA STANDARD/NORME/NORM	RISULTATO RESULT/RÉSULTAT/ERGEBNIS
J	Determinazione della resistenza all'usura BCA Determination of abrasion resistance BCA Détermination de la résistance à l'usure BCA Bestimmung des Verschleißwiderstandes nach BCA	UNI EN 13892/4	Classe\Class\Klasse AR0,5 max50y (50y = 0,05 mm)
	Determinazione della forza di adesione Determination of bond strength Détermination de la force d'adhésion Messung der Haftfestigkeit im Abreißversuch	UNI EN 13892-8	2,2 N\mm²
<u> </u>	Determinazione della Resistenza a Flessione Determination of flexural strength Determination de la resistance a la flexion Bestimmung der Biegezugfestigkeit	UNI EN 13892-2:2005	9,66 N\mm²
KG	Determinazione della Resistenza a Compressione Determination of compressive strength Determination de la resistance a la compression Bestimmung der Druckfestigkeit	UNI EN 13892-2:2005	41,80 N\mm²
8	Classificazione reazione al fuoco Classification fire reaction Réaction au feu Klassifizierung von Bauprodukten und Bauarten zu ihrem Brandverhalten	UNI EN 13501	Classe\class\ Klasse A1



ALL WITHIN A FEW MILLIMETERS

With a maximum thickness of 4-7 mm, LIXIO is the ideal solution for overlaying:

- ✓ concrete
- ✓ ceramic
- √ marble
- ✓ sand cementscreeds.





LIXIO® MARBLE BLEND AVAILABLE AGGREGATES

LIXIO® MARBLE BLEND can be provided in different colors:

- ✓ Carrara White (White)
- √ Botticino (Ivory)
- √ Occhialino (Gray)
- √ Black Ebony (Black)













TRAINING YOURS OUR FIRST AIM

THE CEMENT BASE COLOURS

Same colours as Microtopping. Colour pack-c is available in 25 colours.





EXAMPLES OF COLOUR COMBINATIONS





SURFACE FINISH

The finish will vary, depending on the level of aggregate exposure.







WET OR DRYGRINDING

GRIT36 \rightarrow 100 \rightarrow 200









